



Model No.	External (mm) W*D*H	Capacity (L)	Operating Temp. (°C)	Rated(V) Current(A)	No. of shelves	Weight NW./GW.	Shipping dimension
CRA-120-S-SD	1200×610×850	210	+2~6	220/2.5	2	87/91 kgs	1260*670*880
CRA-150-S-SD	1500×610×850	280	+2~6	220/2.6	2	99/103 kgs	1560*670*880

FEATURES:**REFRIGERATION SYSTEM**

- Operating temperature: +2~6°C, under room temperature of 38°C.
- Fan forced evaporator cooling.
- Self-contained refrigeration system in the right side.
- Automatic evaporation of the defrost water by using the high pressure hot gas of the copper pipe.

CONSTRUCTION

- 55mm all round insulation with high density PU (40kg/m³).
- High quality international brand compressor: Embraco aspera compressor.
- The reduced dimension of compressor section provides a bigger inside space of the counter.
- Waterproof control panel easy to read and control.
- Door construction for compressor section for easy maintenance.
- Soft closing doors.
- Wide magnetic gasket gives effective seal and is removable for easy cleaning and maintenance.

OPTION

- Stainless steel splash-back to prevent spillage behind the counter.
- Internal lighting.
- Standard stainless steel bullet feet, adjustable from 135 to 165mm, castors with 130mm height is optional.